1		AMENDMENTS TO THE CLAIMS		
2				
3	Th	This listing of claims will replace all prior versions, and listings, of claims in the		
4	ap	application:		
5				
6	<u>Li</u>	Listing of Claims		
7				
8	1.	1. (Original)A method of obtaining a digital code representative of a skin-covered		
9		body part, the method including:		
10		- acquiring an image of the skin-covered body part, the image including a		
11 12		plurality of pixels, each pixel having an associated shade value in a range of shade values;		
13		- identifying a plurality of subsets of pixels from the plurality of pixels, each		
14		subset of pixels including at least two pixels having a common one of a		
15		plurality of designated shade values in the range of shade values;		
16		- for each of a plurality of combinations of pixels taken from the pixels in the		
17		subsets of pixels, determining a geometric measure of the pixels in said		
18		combination;		
19		- encoding the geometric measures into a digital code for the skin-covered body		
20		part.		
21				
22	2.	(Original) The method defined in claim 1, wherein said acquiring an image of the		
23		skin-covered body part is performed by a CMOS charge-coupled device.		
24				
25	3.	(Original) The method defined in claim 1, wherein the image is derived from a		
26		live scan of the skin-covered body part pressed onto a platen.		
27				
28	4.	(Original) The method defined in claim 1, wherein said identifying a plurality of		
29		subsets of pixels from the plurality of pixels includes identifying a first subset of		
30		pixels and identifying a second subset of pixels.		
31				
32	5.	(Original) The method defined in claim 4, wherein said identifying a first subset		
33		of pixels includes:		
34		- identifying a first pixel having any of the designated shade values;		

1		- identifying a second pixel having the same designated shade value as the first
2		pixel;
3		wherein the first subset of pixels includes said first and second pixels.
4		
5	6.	(Original) The method defined in claim 5, wherein said identifying a second
6		subset of pixels includes:
7		- identifying a third pixel having any of the designated shade values;
8		- identifying a fourth pixel having the same designated shade value as the third
9		pixel;
10		wherein the second subset of pixels includes said third and fourth pixels.
11		
12	7.	(Original) The method defined in claim 6, wherein identifying the first pixel
13		includes identifying which pixel having the designated shade value is nearest a
14		reference point in the image.
15		
16	8.	(Original) The method defined in claim 7, wherein identifying the second pixel
17		includes identifying which pixel having the designated shade value is nearest the
18		first pixel.
19		
20	9.	(Original) The method defined in claim 7, wherein identifying the second pixel
21		includes identifying which pixel separated from the first pixel by at least a
22		minimum distance and having the designated shade value is nearest the first pixel.
23		
24	10	(Original) The method defined in claim 7, wherein identifying the second pixel
25		includes identifying which pixel having the designated shade value is second
26		nearest the reference point.
27		•
28	11.	(Original) The method defined in claim 7, wherein identifying the second pixel
29		includes identifying which pixel separated from the first pixel by at least a
30		minimum distance and having the designated shade value is second nearest the
31		reference point.
32		•
33	12.	(Original) The method defined in claim 11, wherein the reference point is a center
34		of the image.
		-

1	
2	13. (Original) The method defined in claim 11, wherein the reference point is a corner
3	of the image.
4	
5	14. (Original) The method defined in claim 11, wherein the reference point is a salient
6	feature of the image.
7	
8	15. (Original) The method defined in claim 14, further including identifying the
9	salient feature of the image.
10	
11	16. (Original) The method defined in claim 1, further including consulting a database
12	to obtain the designated shade values.
13	
14	17. (Original) The method defined in claim 1, wherein the plurality of designated
15	shade values are pre-determined and independent of the image.
16	
17	18. (Original) The method defined in claim 1, further including selecting the plurality
18	of designated shade values on a basis of a characteristic of the image.
19	
20	19. (Original) The method defined in claim 1, wherein the designated shade values are
21	grayscale values.
22	
23	20. (Original) The method defined in claim 1, wherein the range of shade values
24	includes 256 grayscale values.
25	
26	21. (Original) The method defined in claim 1, wherein each said combination of
27	pixels includes a respective first pixel and a respective second pixel, and wherein
28	determining a geometric measure of the pixels in a particular one of the plurality
29	of combinations includes determining a distance between the respective first pixel
30	and the respective second pixel.
31	
32	22. (Original) The method defined in claim 21, wherein said determining a distance
33	between the respective first pixel and the respective second pixel includes

1	determining a number of pixels separating the respective first pixel and the
2	respective second pixel.
3	
4	23. (Original) The method defined in claim 21, wherein said determining a distance
5	between the respective first pixel and the respective second pixel includes
6	determining a first number of pixels separating the respective first pixel and the
7	respective second pixel along a first direction and determining a second number of
8	pixels separating the respective first pixel and the respective second pixel along a
9	second direction orthogonal to the first direction.
10	
11	24. (Original) The method defined in claim 1, wherein each said combination of
12	pixels includes at least three respective pixels.
13	
14	25. (Original) The method defined in claim 24, wherein determining a geometric
15	measure of the pixels in a particular one of the plurality of combinations includes
16	determining an average distance among all pairs of the at least three respective
17	pixels.
18	
19	26. (Original) The method defined in claim 24, wherein determining a geometric
20	measure of the pixels in a particular one of the plurality of combinations includes
21	determining an area of a polygon constructed from the at least three respective
22	pixels.
23	
24	27. (Original) The method defined in claim 24, wherein determining a geometric
25	measure of the pixels in a particular one of the plurality of combinations includes
26	determining an average distance to a center of mass of the at least three respective
27	pixels.
28	
29	28. (Original) The method defined in claim 1, wherein each combination of pixels
30	includes a plurality of pixels taken from the same subset of pixels.
31	
32	29. (Original) The method defined in claim 1, wherein all the pixels in a particular one
33	of the combinations of pixels are taken from the same subset of pixels.

1	30. (Original) The method defined in claim 1, wherein each combination of pixels
2	includes at least two pixels taken from different subsets of pixels.
3	
4	31. (Original) The method defined in claim 1, wherein said encoding the geometric
5	measures into a digital code includes concatenating the geometric measures into
6	the digital code.
7	
8	32. (Original) The method defined in claim 1, further including encoding the
9	designated shade values into the digital code.
10	
11	33. (Original) The method defined in claim 1, further including encrypting the digital
12	code.
13	
14	34. (Original) The method defined in claim 1, wherein the skin-covered body part
15	includes a finger tip.
16	
17	35. (Original) The method defined in claim 1, wherein the skin-covered body part
18	does not includes a finger tip.
19	
20	36. (Original) The method defined in claim 1, wherein the skin-covered body part
21	includes a nose tip.
22	
23	37. (Original) The method defined in claim 1, wherein the skin-covered body part
24	includes a palm of a hand.
25	
26	38. (Original) The method defined in claim 1, wherein the skin-covered body part
27	includes an ear.
28	
29	39. (Original) A computer-readable storage medium containing a program element for
30	execution by a computing device to implement a method of obtaining a digital
31	code representative of a skin-covered body part, the program element including:
32	- program code means for acquiring an image of the skin-covered body part, the
33	image including a plurality of pixels, each pixel having an associated shade
34	value in a range of shade values;

1	-	program code means for identifying a plurality of subsets of pixels from the		
2		plurality of pixels, each subset of pixels including at least two pixels having a		
3		common one of a plurality of designated shade values in the range of shade		
4		values;		
5	-	program code means for determining, for each of a plurality of combinations		
6		of pixels taken from the pixels in the subsets of pixels, a geometric measure of		
7		the pixels in said combination;		
8	-	program code means for encoding the geometric measures into a digital code		
9		for the skin-covered body part.		
10				
11 12	40. (Original) An apparatus for obtaining a digital code representative of a skin- covered body part, the apparatus including:			
13	_	means for acquiring an image of the skin-covered body part, the image		
14		including a plurality of pixels, each pixel having an associated shade value in a		
15		range of shade values;		
16	-	means for identifying a plurality of subsets of pixels from the plurality of		
17		pixels, each subset of pixels including at least two pixels having a common		
18		one of a plurality of designated shade values in the range of shade values;		
19	-	means for determining, for each of a plurality of combinations of pixels taken		
20		from the pixels in the subsets of pixels, a geometric measure of the pixels in		
21		said combination;		
22	-	means for encoding the geometric measures into a digital code for the skin-		
23		covered body part.		
24				
25	41-90.	(Cancelled)		
26				
27				
28				
29				
30				
31				
32				
33				
34				